



# SAFETY DATA SHEET

Preparation Date: 9/27/2013 Revision date 8/26/2019 Revision Number: G10

### 1. IDENTIFICATION

Product identifier

Product code: ET107

Product Name: DEHYDRATED ALCOHOL, 200 PROOF, USP

Other means of identification

**Synonyms:** Absolute ethanol

Alcohol

Alcohol dehydrated Alcohol, anhydrous Alcool ethylique (French) Absolute Ethanol 200 proof

Ethanol

Ethyl alcohol anhydrous

Ethyl hydrate Ethyl hydroxide Fermentation alcohol Dehydrated Alcohol

Ethanol, undenatured 200 proof

Ethanol 200 proof Ethyl alcohol

Alcohol etílico (Spanish)

CAS #: 64-17-5
RTECS # KQ6300000
CI#: Not available

Recommended use of the chemical and restrictions on use

Recommended use: Solvent. Perfuming agent. In pharmaceuticals. Inks. In organic synthesis. In

beverages.

Uses advised against No information available

Supplier: Spectrum Chemical Mfg. Corp

14422 South San Pedro St. Gardena, CA 90248

(310) 516-8000

Order Online At: <a href="https://www.spectrumchemical.com">https://www.spectrumchemical.com</a>

Emergency telephone number Chemtrec 1-800-424-9300

Contact Person:Tom Tyner (USA - West Coast)Contact Person:Ibad Tirmiz (USA - East Coast)

### 2. HAZARDS IDENTIFICATION

#### Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Considered a dangerous substance or mixture according to the Globally Harmonized System (GHS)

Product code: ET107 Product name: DEHYDRATED Page 1/14

| Serious eye damage/eye irritation                  | Category 2  |
|--|-------------|
| Reproductive toxicity                              | Category 1A |
| Specific target organ toxicity (single exposure)   | Category 3  |
| Specific target organ toxicity (repeated exposure) | Category 1  |
| Flammable liquids                                  | Category 2  |

#### Label elements

#### Danger

#### Hazard statements

Causes serious eye irritation

May damage fertility or the unborn child

May cause respiratory irritation. May cause drowsiness or dizziness

Causes damage to organs through prolonged or repeated exposure

Highly flammable liquid and vapor



#### Hazards not otherwise classified (HNOC)

Not Applicable

#### Other hazards

Can burn with an invisible flame

Causes mild skin irritation

### **Precautionary Statements - Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Wash face, hands and any exposed skin thoroughly after handling

Do not breathe mist or vapors

Do not eat, drink or smoke when using this product

Wear protective gloves/protective clothing/eye protection/face protection

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. — No smoking

Keep container tightly closed

Ground container and receiving equipment

Use explosion-proof equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Keep cool

### **Precautionary Statements - Response**

IF exposed or concerned: Get medical attention

In case of fire: Use CO2, dry chemical, or foam to extinguish.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

If skin irritation occurs: Get medical attention

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or physician if you feel unwell.

#### **Precautionary Statements - Storage**

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Product code: ET107 Product name: DEHYDRATED Page 2 / 14
ALCOHOL. 200 PROOF. USP

#### **Precautionary Statements - Disposal**

Dispose of contents and container to an approved waste disposal plant in accordance with local, regional, national and international regulations as applicable

#### 3. COMPOSITION/INFORMATION ON INGREDIENTS

| Component               | CAS No  | Weight-% |
|-------------------------|---------|----------|
| Ethyl Alcohol 200 proof | 64-17-5 | 100      |

### 4. FIRST AID MEASURES

First aid measures

General Advice: National Capital Poison Center in the United States can provide assistance if you

have a poison emergency and need to talk to a poison specialist. Call

1-800-222-1222.

**Skin Contact:** Wash off immediately with soap and plenty of water removing all contaminated clothing and

shoes. Get medical attention. If skin irritation persists, call a physician.

**Eye Contact:** Flush eyes with water for 15 minutes. Get medical attention.

Inhalation: Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial

respiration. Get medical attention.

**Ingestion:** Do not induce vomiting without medical advice. Never give anything by mouth to an

unconscious person. Consult a physician if necessary.

Most important symptoms and effects, both acute and delayed

Symptoms Causes eye irritation

May cause skin irritation

May cause irritation of respiratory tract

Dyspnea (Difficulty breathing and shortness of breath)

Central nervous system effects

Dizziness Drowsiness Headache Ataxia

Staggering gait Nausea Vomiting

May cause cardiovascular effects

Indication of any immediate medical attention and special treatment needed

Notes to Physician: Treat symptomatically.

**Protection of first-aiders** 

First-Aid Providers: Avoid exposure to blood or body fluids. Wear gloves and other necessary protective clothing. Dispose of contaminated clothing and equipment as bio-hazardous waste.

### 5. FIRE-FIGHTING MEASURES

**Extinguishing Media** 

Suitable Extinguishing Media: Carbon dioxide (CO2). Dry chemical. Alcohol-resistant foam. Water spray.

Product code: ET107 Product name: DEHYDRATED Page 3 / 14
ALCOHOL, 200 PROOF, USP

Unsuitable Extinguishing Media: Do not use a solid (straight) water stream as it may scatter

and spread fire.

Specific hazards arising from the chemical

Hazardous combustion products Carbon Monoxide, Carbon Dioxide.

**Specific hazards** Flammable. May be ignited by heat, sparks or flames.

Material can burn with invisible flame. Vapor may travel considerable distance to source of ignition and flash back. Vapors may form explosive mixtures with air. Most vapors are heavier than air. They will spread along the ground and collect in low or confined areas (sewers, basements, tanks). Container explosion may occur under fire conditions or when heated. Fire may produce irritating,

corrosive and/or toxic gases.

**Special Protective Actions for Firefighters** 

Specific Methods: No information available

**Special Protective Equipment for Firefighters:** As in any fire, wear self-contained breathing apparatus

pressure-demand, MSHA/NIOSH (approved or equivalent)

and full protective gear

### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions: Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Avoid

contact with skin, eyes and clothing. Use personal protective equipment. Remove all sources of ignition. Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use spark-proof tools and explosion-proof equipment. In case of large spill, water spray or vapor suppressing foam may be used to reduce vapors, but may not prevent ignition in closed

spaces.

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Prevent entry into waterways,

sewers, basements or confined areas.

Methods and material for containment and cleaning up

**Methods for containment** Stop leak if you can do it without risk. Absorb spill with inert material (e.g.

vermiculite, dry sand or earth). In case of large spill, dike if needed. Dike far

ahead of liquid spill for later disposal.

**Methods for cleaning up**Use appropriate tools to put the spilled material in a suitable chemical waste

disposal container. Use only non-sparking tools. Clean contaminated surface

thoroughly.

### 7. HANDLING AND STORAGE

### Precautions for safe handling

#### **Technical Measures/Precautions:**

Provide sufficient air exchange and/or exhaust in work rooms. Remove all sources of ignition. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Keep away from incompatible materials.

Product code: ET107 Product name: DEHYDRATED Page 4 / 14
ALCOHOL, 200 PROOF, USP

### Safe Handling Advice:

Wear personal protective equipment. Use only in well-ventilated areas. Avoid contact with skin, eyes and clothing. Keep away from heat and sources of ignition. Do not breathe vapors or spray mist. Do not ingest. When using do not smoke. Handle in accordance with good industrial hygiene and safety practice.

### Conditions for safe storage, including any incompatibilities

### **Technical Measures/Storage Conditions:**

Keep container tightly closed in a dry and well-ventilated place. Store at room temperature in the original container. Sensitive to light. Store in light-resistant containers. Keep away from heat and sources of ignition. Store in a segregated and approved area. Store away from incompatible materials.

### **Incompatible Materials:**

Oxidizing agents

Acids

Alkali Metals

Halogens

Caustics

isocyanates

Metals

**Bases** 

Acid anhydrides

Acid chlorides

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

## National occupational exposure limits

#### **United States**

| Component               | CAS No  | OSHA           | NIOSH          | ACGIH         | AIHA WEEL |
|-------------------------|---------|----------------|----------------|---------------|-----------|
| Ethyl Alcohol 200 proof | 64-17-5 | 1000 ppm TWA   | 1000 ppm TWA   | 1000 ppm STEL | None      |
|                         |         | 1900 mg/m³ TWA | 1900 mg/m³ TWA |               |           |

#### Canada

| Component               | CAS No  | Canada - Alberta               | Canada - British<br>Columbia | Canada - Ontario | Canada - Quebec                    |
|-------------------------|---------|--------------------------------|------------------------------|------------------|------------------------------------|
| Ethyl Alcohol 200 proof | 64-17-5 | 1000 ppm TWA<br>1880 mg/m³ TWA | 1000 ppm STEL                | 1000 ppm STEL    | 1000 ppm TWAEV<br>1880 mg/m³ TWAEV |

### **Australia and Mexico**

| Component               | CAS No  | Australia                  | Mexico        |
|-------------------------|---------|----------------------------|---------------|
| Ethyl Alcohol 200 proof | 64-17-5 | 1000 ppm TWA               | 1000 ppm STEL |
|                         |         | 1880 mg/m <sup>3</sup> TWA | * *           |

#### Appropriate engineering controls

**Engineering measures to reduce exposure:** 

Ensure adequate ventilation. Provide exhaust ventilation or other engineering controls to keep the airborne

concentrations of vapors and mist below their respective

threshold limit value.

Individual protection measures, such as personal protective equipment

Product code: ET107 Product name: DEHYDRATED Page 5 / 14
ALCOHOL, 200 PROOF, USP

### **Personal Protective Equipment**

Eye protection: Goggles Safety glasses with side-shields.

Chemical resistant apron Skin and body protection:

Long sleeved clothing

Gloves

Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Respiratory protection:

Hygiene measures: Avoid contact with skin, eyes and clothing. When using, do not eat, drink or

smoke. Wash hands before breaks and immediately after handling the product

Density (g/cm3):

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Appearance: Color:

Liquid No information available. Clear. Colorless.

Odor: Taste **Formula** CH3CH2OH

Mild. Pleasant. Alcoholic. Like wine or Pungent. Burning.

whiskey. Ethereal.

Molecular/Formula weight (g/mole): Flammability (solid, gas) Flashpoint (°C/°F):

46.07 no data available 12-14 °C/53.6-57.2 °F 15.8-18 °C/60.44-64.4 °F

Autoignition Temperature (°C/°F): Flash Point Tested according to: **Lower Explosion Limit (%):** 3.3%

363-426 °C/685.4-798.8 °F Closed cup

Open cup

**Upper Explosion Limit (%):** Melting point/range(°C/°F): Decomposition temperature(°C/°F):

-114.1-117.3 °C/-173.38-179.14 °F No information available 19%

Boiling point/range(°C/°F): **Bulk density:** 

78-79 °C/172.4-174.2 °F No information available No information available

Specific gravity: Hq

Vapor pressure @ 20°C (kPa): 0.789 @ 20 °C No information available 5.7-5.866

**Evaporation rate:** Vapor density: VOC content (q/L):

No information available 1.59 789

Odor threshold (ppm): Partition coefficient **Viscosity:** 

No information available 5-10 (recognition) (n-octanol/water):

84 (tolerance) -0.31

Miscibility: Solubility:

Miscible with water Very soluble in water Miscible with Acetone Soluble in Benzene

Miscible with Ether Miscible with Benzene

Miscible with glacial Acetic Acid Miscible with many organic solvents

### 10. STABILITY AND REACTIVITY

#### Reactivity

When Ethanol comes in contact with Sodium, it liberates flammable hydrogen gas

It can react vigorously or explosively with acid hydrides or acid chlorides

It reacts with alkali metals to liberate flammable hydrogen gas

It reacts with acetyl bromide to evolve hydrogen bromide

It reacts with ammonia + silver nitrate to form silver nitride and silver fulminate

Product code: ET107 **Product name: DEHYDRATED** Page 6/14

Ethyl alcohol can react with freshly cut/etched/scratched aluminum with the evolution of heat and release of hydrogen gas. The Ethyl alcohol has to be on the aluminum surface as it is being cut/scratched/etched

Ethyl Alcohol reacts vigorously with acetyl chloride.

Ethyl alcohol reacts with silver (I) oxide + ammonia or hydrazine to form silver nitride and silver fulminate

Ethanol ignites and then explodes on contact with the following compounds: acetic anhydride + sodium hydrosulfate, disulfuric acid + nitric acid, phosphorus (III) oxide, platinum, potassium tert-butoxide + acids

Ethanol rapidly absorbs moisture from the air. Can react vigorously/explosively with oxidizers. Ethanol can react vigorously/explosively with the following: ammonium hydroxide & silver oxide, chlorine or chlorine oxides, perchlorates (barium perchlorate, chloryl perchlorate, magnesium perchlorate (forms ethyl perchlorate), nitrosyl perchlorate, potassium perchlorate, silver perchlorate, uranyl perchlorate), acetic anhydride, acetyl bromide (evolves hydrogen bromide), acetyl chloride, aluminum sesquibromide ethylate, bromine pentafluoride, calcium hypochlorite, chromic anhydride, , chromium trioxide, chromyl chloride, cyanuric acid + water, dichloromethane + sulfuric acid + nitrate (or) nitrite, manganese perchlorate + 2,2-dimethoxy propane, dioxygen difluoride, disulfuryl difluoride, fluorine nitrate, hydrogen peroxide, iodine heptafluoride, manganese heptoxide, iodine + methanol + mercuric oxide, iodine + Phosphorus (forms ethane iodide), mercuric nitrate, nitric acid, perchloric acid, permanganic acid, peroxodisulfuric acid, platinum black, potassium dioxide, potassium permanganate, potassium superoxide, potassium tert-butoxide, ruthenium(VIII) oxide, silver +nitric acid (forms silver fulminate), silver nitrate (forms ethyl nitrate), silver peroxide, sodium hydrazide, hydrogen peroxide + sulfuric acid, sulfuric acid + permanganates, uranium hexafluoride, sulfuric acid + sodium dichromate, tetrachlorisilane + water, silver & nitric acid, tetraphosphorus hexaoxide

**Chemical stability** 

**Stability:** Stable under recommended storage conditions.

Possibility of Hazardous Reactions: Hazardous polymerization does not occur

<u>Conditions to avoid:</u> Heat. Ignition sources. Incompatible materials.

Incompatible Materials: Oxidizing agents

Acids

Alkali Metals Halogens Caustics isocyanates Metals Bases

Acid anhydrides Acid chlorides

**Hazardous decomposition** 

products:

Carbon monoxide. Carbon dioxide. When heated to decomposition it emits acrid

smoke and irritating fumes.

Other Information

Corrosivity: No information available

Special Remarks on Corrosivity: No information available

### 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

**Principal Routes of Exposure:** Ingestion. Skin. Eyes. Inhalation.

**Acute Toxicity** 

**Component Information** 

Product code: ET107 Product name: DEHYDRATED Page 7 / 14
ALCOHOL. 200 PROOF. USP

Ethyl Alcohol 200 proof

CAS No 64-17-5

LD50/oral/rat = 7060 mg/kg Oral LD50 Rat

LD50/oral/mouse = 3450 mg/kg Oral LD50 Mouse

**LD50/dermal/rabbit** = No information available

**LD50/dermal/rat** = No information available

LC50/inhalation/rat = 124.7 mg/L Inhalation LC50 Rat 4 h

LC50/inhalation/mouse = 39000 mg/m<sup>3</sup> 4 h

Other LD50 or LC50information = >60000 ppm Inhalation LC50 Mouse 1 h

5900 mg/m³ Inhalation LC50 Rat 6 h 20000 ppm Inhalation LC50 Rat 10 h 5560 mg/kg Oral LD50 Guinea Pig 6300 mg/kg Oral LD50 Rabbit

#### **Product Information**

LD50/oral/rat =

Value - Acute Toxicity = 7060 mg/kg

LD50/oral/mouse =

Value - Acute Tox = 3450 mg/kg

LD50/dermal/rabbit

Value - Acute Toxicity = No information available

LD50/dermal/rat

**VALUE - Acute Tox =** No information available

LC50/inhalation/rat

VALUE-Vapor = 124.7 mg/l (4-hr)
VALUE-Gas = No information available
VALUE-Dust/Mist = No information available

LC50/Inhalation/mouse

VALUE-Vapor = 39 mg/l (4-hr)

**VALUE - Gas =** No information available

VALUE - Dust/Mist = No information available

**Symptoms** 

**Skin Contact:** Mildly to moderately irritating to the skin.

**Eye Contact:** Causes serious eye irritation. Causes moderate to severe eye irritation.

**Inhalation** May cause irritation of respiratory tract. Symptoms may include coughing and

shortness of breath. May cause nausea and headache. It may affect

behavior/central nervous system (ataxia, general anesthetic, drowsiness). May affect respiration (respiratory depression). Inhalation of high concentrations of vapor may cause anesthetic effects. Inhalation of high concentrations of vapors

may cause dizziness or suffocation. May affect the brain.

**Ingestion** Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. May

cause gastritis. May cause loss of appetite. May cause flushed skin. May affect the cardiovascular system (change in heart rate). May affect the cardiovascular system (hypotension or hypertension, tachycardia, dysrhythmias). It may affect behavior/central nervous system (excitation, mild euphoria, excessive talking, fatigue, headache, dizziness, drowsiness, staggaring gait, ataxia, hallucinations,

Product code: ET107 Product name: DEHYDRATED Page 8/14

slurred speech, amnesia, confusion, release of inhibitions, agressive behavior, convulsions, coma). May affect respiration (dyspnea, respiratory depression). It may affect the brain. May affect liver. May affect the blood. May affect the endocrine system. It may affect the spleen. May affect urinary system (kidneys).

**Aspiration hazard** 

No information available.

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Chronic Toxicity Prolonged or repeated skin contact may cause dermatitis, and dryness and

cracking of the skin. Prolonged or repeated ingestion may affect behavior/central nervous system. Prolonged or repeated ingestion may affect metabolism (cause anorexia, weight loss). Prolonged or repeated ingestion may affect the liver (fatty liver degeneration, cirrhosis of the liver. Prolonged or repeated ingestion may affect the cardiovascular system. Prolonged or repeated inhalation may affect the

liver.

**Sensitization:** No information available.

Mutagenic Effects: May affect genetic material based on animal test data

Mutations in microorganisms

Experiments with bacteria and/or yeast have shown mutagenic effects

Cytogenic analysis - hamster ovary Cytogenic Analysis (Hamster embryo) Cytogenic analysis - human leukocyte Cytogenic Analysis: human lymphocyte Sister Chromatid Exchange - Hamster ovary Sister Chromatid Exchange (human lymphocyte)

Carcinogenic effects:

Equivocal tumorigenic agent by Registry of Toxic Effects of Chemical Substances (RTECS) criteria. Confirmed Animal Carcinogen with Unknown Relevance to Humans.

| Component               | CAS No | IARC  | ACGIH -<br>Carcinogens   | NTP        | OSHA HCS -<br>Carcinogens | Australia -<br>Notifiable<br>Carcinogenic<br>Substances | Australia -<br>Prohibited<br>Carcinogenic<br>Substances |
|-------------------------|--------|---|--|------------|---------------------------|---|---|
| Ethyl Alcohol 200 proof |        | Monograph<br>100E [2012] in<br>alcoholic<br>beverages | A3 Confirmed<br>Animal<br>Carcinogen<br>with Unknown<br>Relevance to<br>Humans | Not listed | Present                   | Not listed  | Not listed  |

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

(In alcoholic beverages)

NTP (National Toxicology Program)

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

Reproductive toxicity

May damage fertility or the unborn child

Reproductive Effects: Causes adverse reproductive effects

Developmental Effects: May cause harm to the unborn child

May cause adverse developmental effects

Product code: ET107 Product name: DEHYDRATED Page 9 / 14
ALCOHOL, 200 PROOF, USP

**Teratogenic Effects:** Causes birth defects (teratogenic effects)

**Specific Target Organ Toxicity** 

STOT - single exposure STOT - repeated exposure

Target Organs:

respiratory system. central nervous system.

Causes damage to organs through prolonged or repeated exposure. Skin. Liver. Central nervous system. Nervous system. Heart. Reproductive

System.

#### 12. ECOLOGICAL INFORMATION

**Ecotoxicity** 

**Ecotoxicity effects:** Aquatic environment.

Ethyl Alcohol 200 proof - 64-17-5

Fish

LC50: 12.0 - 16.0mL/L (96h, Oncorhynchus mykiss) LC50: >100mg/L (96h, Pimephales promelas) LC50: 13400 - 15100mg/L (96h, Pimephales promelas)

Crustacea LC50: 9268 - 14221mg/L (48h, Daphnia magna) EC50: =2mg/L (48h, Daphnia

magna) EC50: =10800mg/L (24h, Daphnia magna)

Persistence and degradability: No information available

**Bioaccumulative potential:** No information available.

Mobility in soilNo information availableOther adverse effectsNo information available.

### 13. DISPOSAL CONSIDERATIONS

### **Disposal Methods**

#### Waste from residues / unused products:

Waste must be disposed of in accordance with Federal, State and Local regulation.

#### Contaminated packaging:

Empty containers should be taken for local recycling, recovery or waste disposal

| Component               | CAS No  | RCRA - F Series<br>Wastes | RCRA - K Series<br>Wastes | RCRA - P Series<br>Wastes | RCRA - U Series<br>Wastes |
|-------------------------|---------|---------------------------|---------------------------|---------------------------|---------------------------|
| Ethyl Alcohol 200 proof | 64-17-5 | None                      | None                      | None                      | None                      |

### 14. TRANSPORT INFORMATION

DOT

UN-No: UN1170
Proper Shipping Name: Ethanol

Hazard Class 3

Subsidiary Class No information available

Packing group: || Emergency Response Guide 127

Number

Marine Pollutant
DOT RQ (lbs):
No information available

Special Provisions 24, IB2, T4, TP1

Product code: ET107 Product name: DEHYDRATED Page 10 / 14

Symbol(s): No information available UN1170, Ethanol, 3, II

TDG (Canada)

UN-No: UN1170
Proper Shipping Name: Ethanol

Hazard Class 3

Subsidiary Risk: No information available

Packing Group:

Marine PollutantNo Information availableDescription:UN1170, Ethanol, 3, II

ADR

UN Number UN1170
Proper Shipping Name: Ethanol
Transport hazard class(es) 3
Packing group II

Subsidiary Risk: No information available

Special Provisions 144, 601

**Description:** UN1170, Ethanol, 3, II

**IMDG** 

UN-No: UN1170
Proper Shipping Name: Ethanol

Hazard Class: 3

Subsidiary Risk: No information available

Packing Group:

Marine Pollutant No information available

EMS: F-E Special Provisions 144

**Description** UN1170, Ethanol, 3, II

**RID** 

UN Number UN1170
Proper Shipping Name: Ethanol
Transport hazard class(es) 3
Subsidiary Risk: 3
Packing group II

Special Provisions 144, 601

**Description:** UN1170, Ethanol, 3, II

ICAO (air)

UN-No: UN1170
Proper Shipping Name: Ethanol

Hazard Class 3

Subsidiary Risk: No information available

Packing Group:

**Description:** UN1170, Ethanol, 3, II

Special Provisions A58, A180, A3

**IATA** 

UN Number UN1170 Proper Shipping Name: Ethanol

Transport hazard class(es) 3

Subsidiary Risk: No information available

Packing group II Precautionary Statements - 3L

Response

Product code: ET107 Product name: DEHYDRATED Page 11 / 14
ALCOHOL, 200 PROOF, USP

Special Provisions Description:

No information available UN1170, Ethanol, 3, II

### 15. REGULATORY INFORMATION

### International Inventories

| Component                  | CAS No  | U.S. TSCA           | KOREA KECL | Philippines (PICCS) | Japan ENCS | China IECSC | Australia<br>(AICS) | EINECS-No.           |
|----------------------------|---------|---------------------|------------|---------------------|------------|-------------|---------------------|----------------------|
| Ethyl Alcohol 200<br>proof | 64-17-5 | Present(ACTI<br>VE) | KE-13217   | Present             | (2)-202    | Present     | Present             | Present<br>200-578-6 |

### **U.S. Regulations**

Ethyl Alcohol 200 proof

Massachusetts RTK: Present

New Jersey RTK Hazardous Substance List: 0844

Pennsylvania RTK: Present

Minnesota - Hazardous Substance List: Present

Louisana Reportable Quantity List for Pollutants: Present (listed as Volatile Organic Compounds)

California Directors List of Hazardous Substances: Present

FDA - Food Additives Generally Recognized as Safe (GRAS): 21 CFR 184.1293

FDA - 21 CFR - Total Food Additives 169.175, 169.176, 169.177, 169.181, 172.340, 172.560, 172.580, 175.105, 176.180,

- List Sourced from EAFUS 176.200, 177.1200, 177.1650, 178.1010, 184.1293, 73.30, 73.345, 73.615

#### California Prop. 65: Safe Drinking Water and Toxic Enforcement Act of 1986.

#### Chemicals Known to the State of California to Cause Cancer:

△WARNING: This product can expose you to chemicals including (see table below) which is (are) known to the State of California to cause cancer. For more information go to www.p65warnings.ca.gov.

### Chemicals Known to the State of California to Cause Reproductive Toxicity:

⚠WARNING: This product can expose you to chemicals including (see table below) which is (are) known to the State of California to cause birth defects or other reproductive harm. For more information go to www.p65warnings.ca.gov.

| Component               | CAS No | Carcinogen  | Developmental Toxicity  | Male         | Female       |
|-------------------------|--------|-------------|---|--------------|--------------|
|                         |        |             |   | Reproductive | Reproductive |
|                         |        |             |   | Toxicity     | Toxicity:    |
| Ethyl Alcohol 200 proof |        | (Ethanol in | developmental toxicity<br>(Ethyl alcohol in alcoholic<br>beverages) |              | Not Listed   |

### **CERCLA/SARA**

| Component               | CAS No  | CERCLA -<br>Hazardous<br>Substances and<br>their Reportable<br>Quantities | Section 302 Extremely Hazardous Substances and TPQs | Section 302 Extremely Hazardous Substances and RQs | Section 313 -<br>Chemical Category | Section 313 -<br>Reporting<br>de minimis |
|-------------------------|---------|---|---|--|------------------------------------|--|
| Ethyl Alcohol 200 proof | 64-17-5 | None  | None  | None   | None                               | None                                     |

#### U.S. TSCA

| Component               |         |                | TSCA 8(d) -Health and Safety<br>Reporting |
|-------------------------|---------|----------------|---|
| Ethyl Alcohol 200 proof | 64-17-5 | Not Applicable | Not Applicable                            |

### Canada

Product code: ET107 Product name: DEHYDRATED Page 12 / 14
ALCOHOL, 200 PROOF, USP

#### WHIMIS 2015 - GHS Classifications

WHMIS 2015 Hazard Classification Information:

Component Ethyl Alcohol 200 proof 64-17-5 ( 100 )

WHMIS 2015 Hazard Classification Flammable liquids - Category 2: H225 Highly flammable liquid and vapour.; Serious Eye Damage/Eye Irritation - Category 2B: H320 Causes eye irritation.

Canada Hazardous Products Regulation This product has been classified according to the hazard criteria of the HPR (Hazardous Products Regulation) and the SDS contains all of the information required by the HPR

### DSL/NDSL

| Component               | CAS No  | Canada (DSL) | Canada (NDSL) |
|-------------------------|---------|--------------|---------------|
| Ethyl Alcohol 200 proof | 64-17-5 | Present      | Not Listed    |

| Component               | CAS No  | CEPA Schedule I - Toxic Substances                          |
|-------------------------|---------|---|
| Ethyl Alcohol 200 proof | 64-17-5 | Not listed  |
| Component               |         | CEPA - 2010 Greenhouse Gases Subject to Mandatory Reporting |
| Ethyl Alcohol 200 proof | 64-17-5 | Not listed  |

### **EU Classification**

### EU GHS - SV - CLP 1272/2008

| Component               | CAS No  | EU GHS - SV - CLP (1272/2008)          |
|-------------------------|---------|--|
| Ethyl Alcohol 200 proof | 64-17-5 | Flammable liquids - Flam. Liq. 2: H225 |
|                         |         | Highly flammable liquid and            |
|                         |         | vapour.603-002-00-5                    |

### EU - CLP (1272/2008)

### R-phrase(s)

R11 - Highly flammable

<u>S -phrase(s)</u> S 7 - Keep container tightly closed.

S16 - Keep away from sources of ignition - No smoking

| Component               | CAS No  |        | Concentration<br>Limits: | Safety Phrases |
|-------------------------|---------|--------|--------------------------|----------------|
| Ethyl Alcohol 200 proof | 64-17-5 | F; R11 | No information           | S(2) S7 S16    |

The product is classified in accordance with Annex VI to Directive 67/548/EEC

### Indication of danger:

F - Highly flammable

Product code: ET107 Product name: DEHYDRATED Page 13 / 14



### **16. OTHER INFORMATION**

Preparation Date: 9/27/2013
Revision date 8/26/2019
Prepared by: Sonia Owen

**Disclaimer:** All chemicals may pose unknown hazards and should be used with caution. This

Safety Data Sheet (SDS) applies only to the material as packaged. If this product is combined with other materials, deteriorates, or becomes contaminated, it may pose hazards not mentioned in this SDS. The physical properties reported in this SDS are obtained from the literature and do not constitute product specifications. Information contained herein does not constitute a warranty, whether expressed or implied, as to the safety, merchantability or fitness of the goods for a particular purpose. Spectrum Chemicals & Laboratory Products, Inc. assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied. It shall be the user's responsibility to develop proper methods of handling and personal protection based on the actual conditions of use. While this SDS is based on technical data judged to be reliable, Spectrum assumes no responsibility for the

completeness or accuracy of the information contained herein.

**End of Safety Data Sheet** 

Product code: ET107 Product name: DEHYDRATED Page 14 / 14